

CCD Imaging Photometer and Colorimeter
PM-1400 Series



Applications

- Brightness and color uniformity testing for any display technology
- Display defect detection for pixel, line and mura defects
- Testing and correction of LED video screens and video walls
- Illumination distribution measurement

Benefits

- Provides quantitative measurements that correspond to human perception of brightness and color
- Fast, accurate luminance and color measurements
- Easy to use measurement control and image analysis software allows detailed data evaluation
- Industry leading warranty and technical support ensure successful applications in both R&D and production


High precision imaging colorimeter for display and light source measurement

The PM-1400F series of imaging photometers and colorimeters delivers an excellent balance of wide dynamic range, high spatial resolution, large field of view, and speed. This makes it the first choice for demanding measurement, calibration and defect detection tasks in both production and laboratory environments. The CCDs used in the PM-1400F series are full-frame CCDs with 100% fill factor, making them ideally suited for resolving small features on instrument panels or keypads, for measuring small features such as the brightness and color of individual LED or OLED pixels or sub-pixels, or for finding small defects, such as display pixel defects.

The PM-1400F series use 14-bit (over 16,000 gray levels), thermoelectrically cooled and temperature stabilized, scientific grade CCDs for accuracy and repeatability. There are three different CCD resolutions available – 768 x 512, 1,536 x 1,024 and 3,072 x 2,048 – each with an optimal application area. For added versatility and measurement speed, the higher resolution CCDs can be operated at lower resolutions with electronically binned pixels. In addition, each model is available in either a photometric or a colorimetric configuration.

All F-Series cameras include motorized filter wheels, for both the CIE matched filters and a set of internal neutral density filters, and Radiant Imaging's patent-pending precision internal shutter. A wide selection of lenses is available, allowing the field of view and working distance to be tailored to the application. The F-Series models include numerous design improvements over earlier Radiant Imaging photometers and colorimeters to provide enhanced performance, improved reliability, and easier maintenance for their users.

Each PM-1400 series imaging photometer and colorimeter comes with Radiant Imaging's ProMetric control and analysis software, which provides complete measurement control and an extensive suite of image analysis functions. ProMetric software functions can be externally accessed through PMEngine™.Net (Framework 2.0) controls so users can build custom test and analysis sequences.






Key Features

- 14-bit, full frame, temperature stabilized CCD sensor
- Integrated CIE matched color filters and neutral density filters
- Precision, patent-pending, high speed internal shutter
- Broad selection of CCD resolutions and lenses
- Complete ProMetric control and analysis software support

Specification*

Spatial measurement capabilities	Luminance, Radiance, Illuminance, Irradiance, Luminous Intensity, Radiant Intensity, CIE Chromaticity Coordinates, L*a*b* Color Scale, Correlated Color Temperature (CCT), Dominant Wavelength		
Units	Footlambert, Cd/cm ² , Cd/m ² , Nit, Mnit, mnit, W/sr/m ² , W/sr/ft ² , W/sr/cm ² , mW/sr/m ² , Footcandles, Lux, mLux, Mlux, Lux-Sec, W/m ² , W/ft ² , W/cm ² , mW/m ² , MW/m ² , W-Sec/m ² , Candela, W/sr, CIE (x,y) and (u', v'), Kelvin (CCT)		
CCD resolution	768x512, 1,536x1,024, or 3,072x2,048 pixels		
CCD A/D dynamic range	14 bits = 16,384 gray scale levels		
Luminance range	0.01 nit minimum 10 ¹⁰ nit maximum with optional ND filters		
System accuracy (PM-1000-0 imaging photometer)	Illuminance	± 3% ₁	
	Luminance (Y)	± 3% ₁	
	Color Coordinates (x,y)	± 0.003 ₁	
Short-term repeatability	Illuminance	± 0.5% ₂	
	Luminance (Y)	± 0.5% ₂	
	Color Coordinates (x,y)	± 0.0006 ₂	
Interface	USB2.0		
Minimum measurement time (for 100 cd/m ²), photopic and color	768x512 CCD	1.8 seconds	5.5 seconds
	1,536x1,024 CCD	2.3 seconds	8 seconds
	3,072x2,048 CCD	7 seconds	25 seconds
Camera field of view	768x512 CCD	1° to 26°	
	1,536x1,024 CCD	3° to 50°	
	3,072x2,048 CCD	5° to 87°	
Dimensions	154mm x 242mm x 200mm (HxWxD)		
Weight	4.8kg		
Operating temperature	0–30° C		
Operating humidity	20 - 70% non-condensing		

* Specifications subject to change without notice
 Applicable only for color series



System Requirements

- 2.0 GHz or faster processor
- 1GB or greater RAM
- Windows® 2000, XP or Vista
- USB 2.0 interface

¹ Based on Illuminant A, D 65, or user calibration for specific spectra. Based on a virtual detector size of 100 pixels. Specification is for every point within the field of view of the camera.

² At every point within the field of view of the camera, based on a virtual detector size of 100 pixels.